


引脚定义:

PIN	SYMBOL
1	CS1
2	RST
3	RS
4	WR
5	RD
6	D0
7	D1
8	D2
9	D3
10	D4
11	D5
12	D6
13	D7
14	VDD
15	VSS
16	VO
17	XV0
18	VG
19	C86
20	P/S

DISPLAY TYPE: FSTN/POSITIVE
 POLARIZER: TRANSMISSIVE
 VIEWING DIRECTION: 6:00-CLOCK
 DRIVE METHOD: 1/49DUTY,1/8BIAS
 OPERATING VOLTAGE:8.2V
 OPERATING TEMP: -20 TO 70 Deg.C
 STORAGE TEMP: -30 TO 80 Deg.C
 CONNECTOR: COG
 UNSIGNED TOLERANCE: ±0.20



REVISION RECORD		DATE	Radiant-way Technoly Inc.	
1	第1版		TITLE:LCD CUTLINE DIMENSION	未标注公差为: ±0.2
2			Model No: RDB12848G-943F	PEG(3)
3			Part No: F0G	VER: A
4			DRAWN	DATE 2020/4/14 SHEET 1/1
5			CHECKED	DATE 2020/4/15 UNIT: mm
6			APPROVED	DATE SCALE 1:1