


接口定义

NO.	SYMBOL
1	CSB
2	RST
3	A0
4	SCK
5	SDA
6	VDD
7	VSS
8	VB0-
9	VB0+
10	VB1-
11	VB1+
12	VLCD
13	LEDA
14	LEDK

NOTES:

- | | |
|---------------------------|---------------|
| 1. DISPLAY TYPE: | FSTN/POSITIVE |
| 2. OPERATING VOLTAGE: | VDD=3.3V |
| 3. OPERATING TEMPERATURE: | -20°C~70°C |
| 4. STORAGE TEMPERATURE: | -30°C~80°C |
| 5. DRIVE MODE: | 1/64D,1/9B |
| 6. VIEWING DIRECTION: | 6:00 |
| 7. POLARIZER TYPE: | TRANSFLECTIVE |
| 8. CONNECTOR: | COG/UC1604C |
| 9. CUSTOMER No.: | RDB16048G-947 |
| 10. FREQUENCY: | 64HZ |
| 11. Unassigned tolerances | ±0.20. |



REVISION RECORD		DATE	Radiant-way Technology Inc.	
1	第1版	TITLE:LCD CUTLINE DIMENSION		未标注公差为: ±0.2
2		Model No:RDB16048G-947F		PEG (3)
3		Part No: LCD		VER: A
4		DRAWN	DATE	2021/03/10 SHEET 1/1
5		CHECKED	DATE	UNIT: mm
6		APPROVED	DATE	SCALE 1:1