


接口定义:


PIN	DESC
1	ESD
2	VG
3	XV0
4	V0
5	VM
6	VDD
7	VSS
8	VD1
9	CSB
10	IF3
11	IF2
12	IF1
13	RST
14	RD
15	D7
16	D6
17	D5
18	D4
19	D3
20	D2
21	D1
22	D0
23	WR
24	RS
25	ESD

电路框图



说明:

- 2.LCM工作电压VDD=3.3V;
- 3.工作温度-20~+70摄氏度;
- 4.储存温度-30~+80摄氏度;
- 5.视角为6点钟;
- 6.LCD驱动条件为1/160Duty, 1/14Bias;
- 7.背光为白色6颗LED侧背光, 3.0V, 48~120mA;
- 8.LCD底色可选白底黑字或蓝底白字。
- 9.IC型号: ST7586S
- 10.连接方式: COG(Chip On Glass)



REVISION RECORD		DATE	Radiant-way Technology Inc.	
1		TITLE:LCD CUTLINE DIMENSION		
2		Model No:RDB384160G-973-BN		PEG (3)
3		Part No: FOG+BL		VER: A
4		DRAWN	DATE	2022/1/19 SHEET 1/1
5		CHECKED	DATE	UNIT: mm
6		APPROVED	DATE	SCALE 1:1